




- Stainless steel pump body
- Stainless steel motor shaft
- Stainless steel support base to
- Guarantee a better stability
- Die-cast stainless steel impeller

Model: **BIOX 200/8 AUTO**
 Part number: **N2091020**
 Barcode: **8010583101706**

Submersible pump for waste water and drainage applications. BIOX 200/8 is a professional pump with a stainless steel pump body, motor shaft, impellers and pump base, allowing to leave the pump permanently in water without any risk of corrosion. High reliability thanks to the vortex impeller. Maximum size of impurities: up to 40 mm



APPLICATIONS

Drainage of cesspools, flood water removal and ewage transfer from sump.
 Emptying of septic tanks

ABSORBED POWER	900 W	MAX.DEPTH OF IMMERSION	7 m
VOLTAGE	230 V	MAX.TEMPERATURE OF FLUID	40°C
FLOW RATE	17000 l/h	MAX.SIZE OF IMPURITIES	40 mm
MAX. HEAD	9 m	START / STOP	400 mm / 300 mm
RATED CURRENT	4.1 A	WEIGHT	8.5 kg
PUMP BODY	Stainless Steel	PACKAGING DIMENSIONS	23 x 19.5 x 44 cm
DELIVERY PORT	47,8 mm (1 1/2 M)	PCS PER PALLET	40
MINIMUM DRAINING LEVEL	45 mm	ACCESSORIES	Connector